



eloProg signal output modules 485EPA00S

Product characteristics

- Signal output module with 8/16 configurable control outputs for simple diagnosis
- Pre-assembled T-connector (proprietary 5-way bus) for connection to the base module and other expansion modules simplifies wiring and saves space in the switch cabinet

Article characteristics

Attribute	485EPA00S08	485EPA00S16
Max. switching voltage at control output	24 V DC	
Max. switching current at control output	0.1 A	
Number of configurable electronic safety outputs	8	16
Operating voltage min.	19.2 V DC	
Operating voltage max.	28.8 V DC	
Power consumption	3 W	
Response time	je nach Konfiguration ms	
Operating life	20 Tm	
Dimensions	108 x 22,5 x 114,5 mm (H/B/T)	
Housing material	PA	
Housing colour	Gehäuse schwarz Frontplatte gelb	
Operating temperature min.	-10 °C	
Max. operating temperature	55 °C	
Min. storage temperature	-20 °C	
Max. storage temperature	85 °C	
Relative humidity	10...95 %	
Weight	200 g	280 g
Torque for connection terminals	0.6 N m	
Min. connection cross section	0.5 mm²	
Max. connection cross section	2.5 mm²	
Certified in accordance with	EN ISO 13849-1 IEC 61508 IEC 62061 UL 508 / CSA 22.2	