



Conector circular angular M12 4-5 pinos com anel de acoplamento em plástico

Especificação Técnica

- Resistente à produtos químicos e óleo
- Aprovação ECOLAB
- Elevada classe de proteção e de temperatura de trabalho para atender às demandas de ambientes industriais adversos
- Compatível com todos os sensores elobau e sensores tipo bóia com a conexão adequada

Desenho técnico

IMAGE 1/6

K15.00.




IMAGE 2/6

female M12



IMAGE 3/6

1) _____ **BN**

2) _____ **WH**

3) _____ **BU**

4) _____ **BK**

IMAGE 4/6

K17.00.



IMAGE 5/6

female M12



IMAGE 6/6

1) _____ BN

2) _____ WH

3) _____ BU

4) _____ BK

5) _____ GY

Product options

IMAGE 1/1

ORDERING KEY

K1			Circular connector M12 4-pin/5-pin, angled, with coupling ring, plastic
	5G		Sheath material PVC, black, 4-pin
	5H		Sheath material PUR, black, 4-pin
	7G		Sheath material PVC, black, 5-pin
	7H		Sheath material PUR, black, 5-pin
		001K	Cable length 1m ± 30mm
		003K	Cable length 3m ± 40mm
		005K	Cable length 5m ± 60mm
		000K	Cable length 10m ± 80mm
			Other cable materials and cable lengths on request

Características do artigo

Attribute	K15G...K	K15H...K	K17G...K	K17H...K
Max. switching current per contact	4 A			
Rated impulse withstand voltage (Uimp)	2500 V		1500 V	
Operating voltage max.	250 V DC		125 V DC	
Operating voltage max.	250 V AC		125 V AC	
Cable colour	Black			
Cable material	PVC	PUR	PVC	PUR
Nut material	PA			
Overmould material	PVC	PUR	PVC	PUR
Min. storage temperature	-30 °C	-40 °C	-30 °C	-40 °C
Max. storage temperature	80 °C			
Min. cable temperature range, moving	-5 °C	-25 °C	-5 °C	-25 °C
Max. cable temperature range, moving	80 °C			
Min. cable temperature range, fixed installation	-30 °C	-40 °C	-30 °C	-40 °C
Max. cable temperature range, fixed installation	80 °C			
Torque for nuts	0,6 N m			
Connector type	M12 socket, angled			
Cable length	10 m			
Cable diameter	5 mm	4,7 mm	5,2 mm	5 mm
Number of pins	4		5	
Number of strands	4		5	
Wire cross section	0.34 mm²			
Certified in accordance with	UL/CSA ECOLAB			